


**REUSABLE HYDRAULIC**

**LOW PRESSURE - 100R4, COUPLINGS**

**SPECIFICATIONS**

PRODUCT I.D.		HOSE I.D. (IN.)	NOM. FLG. SIZE (IN.)	"M" FLG. DIA. (IN.)	"T" DROP (IN.)	COUPLING LENGTH (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #						
12C4-12FL90	80557	3/4	3/4	1 1/2	2.13	3.38	2.13
12C4-16FL90	80558	3/4	1	1 3/4	2.13	3.38	2.13
16C4-16FL90	80559	1	1	1 3/4	2.38	3.75	2.44
16C4-20FL90	80561	1	1 1/4	2	2.38	3.75	2.44
20C4-20FL90	80562	1 1/4	1 1/4	2	2.62	4.41	2.59
20C4-24FL90	80565	1 1/4	1 1/4	2 3/8	2.62	4.46	2.64
24C4-24FL90	80563	1 1/2	1 1/2	2 3/8	3.12	4.95	3.06
32C4-32FL90	80564	2	2	2 13/16	4.50	6.88	4.50

**O-Ring Flange 90°**  
CODE 61 – SAE J518




**REUSABLE COUPLINGS FOR 100R2 HOSE**

**SAE 100R2 Type AT, Thin Cover  
Non-Skive Type**

**SPECIFICATIONS**

PRODUCT I.D.			HOSE I.D. (IN.)	THREAD SIZE (IN.)	LENGTH (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #	GATES REFERENCE #				
42504N-102	81247	4C2AT-2RMP	1/4	1/8 - 27	2.30	1.23
42504N-104	81223	4C2AT-4RMP	1/4	1/4 - 18	2.52	1.45
42506N-104	81248	6C2AT-4RMP	3/8	1/4 - 18	2.68	1.45
42506N-106	81224	6C2AT-6RMP	3/8	3/8 - 18	2.53	1.30
42508N-106	81249	8C2AT-6RMP	1/2	3/8 - 18	3.05	1.63
42508N-108	81225	8C2AT-8RMP	1/2	1/2 - 14	3.06	1.64
42508N-112	81251	8C2AT-12RMP	1/2	3/4 - 14	3.13	1.71
42512N-112	81226	12C2AT-12RMP	3/4	3/4 - 14	3.19	1.65
42516N-116	81227	16C2AT-16RMP	1	1 - 11 1/2	3.78	2.04
42520N-120	81228	20C2AT-20RMP	1 1/4	1 1/4 - 11 1/2	4.59	2.49
42524N-124	81252	24C2AT-24RMP	1 1/2	1 1/2 - 11 1/2	5.18	2.68


**NPTF Solid Male**



**SPECIFICATIONS**

PRODUCT I.D.		HOSE I.D. (IN.)	THREAD SIZE (IN.)	LENGTH (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #				
4C2AT-4RMPX	81350	1/4	1/4 - 18	3.18	2.11
6C2AT-6RMPX	81351	3/8	3/8 - 18	3.51	2.27
8C2AT-8RMPX	81352	1/2	1/2 - 14	3.99	2.56
12C2AT-12RMPX	81353	3/4	3/4 - 14	4.27	2.73


**NPTF Swivel Male**



**REUSABLE HYDRAULIC**

**REUSABLE COUPLINGS FOR 100R2 HOSE**


**JIC Solid Male**



**SPECIFICATIONS**

PRODUCT I.D.			HOSE I.D. (IN.)	THREAD SIZE (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #	GATES REFERENCE #			
42504N-504	-	-	1/4	7/16 - 24	1 3/8
42504N-505	-	-	1/4	1/2 - 20	1 3/8
42504N-506	-	-	1/4	9/16 - 18	1 3/8
42506N-506	81342	6C2AT-6RMJ	3/8	9/16 - 18	1 3/8
42506N-508	-	-	3/8	3/4 - 16	1 1/2
42508N-508	81343	8C2AT-8RMJ	1/2	3/4 - 16	1 9/16
42508N-510	81344	8C2AT-10RMJ	1/2	7/8 - 14	1 11/16
42512N-512	81345	12C2AT-12RMJ	3/4	1 1/16 - 12	1 3/4
42516N-516	-	-	1	1 5/16 - 12	1 15/16

**Female JIC  
37° Flare Swivel**




**SPECIFICATIONS**

PRODUCT I.D.			HOSE I.D. (IN.)	THREAD SIZE (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #	GATES REFERENCE #			
42504N-604	81229	4C2AT-4RFJX	1/4	7/16 - 20	1 1/2
42504N-605	81230	4C2AT-5RFJX	1/4	1/2 - 20	1 9/16
42504N-606	-	-	1/4	9/16 - 18	1 5/8
42506N-406	-	-	3/8	5/8 - 18	1 1/2
42506N-606	81231	6C2AT-6RFJX	3/8	9/16 - 18	1 5/8
42506N-608	81232	6C2AT-8RFJX	3/8	3/4 - 16	1 13/16
42508N-608	81233	8C2AT-8RFJX	1/2	3/4 - 16	1 13/16
42508N-610	81234	8C2AT-10RFJX	1/2	7/8 - 14	1 7/8
42512N-610	-	-	3/4	7/8 - 14	1 7/8
42512N-412*	-	-	3/4	1 1/16 - 14	2
42512N-612	81235	12C2AT-12RFJX	3/4	1 1/16 - 12	2
42512N-614	-	-	3/4	1 3/16 - 12	2 1/16
42516N-616	81236	16C2AT-16RFJX	1	1 5/16 - 12	2 5/8
42520N-620	81237	20C2AT-20RFJX	1 1/4	1 5/8 - 12	2 3/4
42524N-624	81254	24C2AT-24RFJX	1 1/2	1 7/8 - 12	3
42532N-632	81255	32C2AT-32RFJX	2	2 1/2 - 12	3 3/4

\* Female SAE (45° flare) swivel

**Female JIC  
37° Flare Swivel  
45° Bent Tube**



**SPECIFICATIONS**

PRODUCT I.D.			HOSE I.D. (IN.)	THREAD SIZE (IN.)	"T" DROP (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #	GATES REFERENCE #				
42504N-684	81354	4C2AT-4RFJX45	1/4	7/16 - 20	0.33	1 7/8
42506N-686	81355	6C2AT-6RFJX45	3/8	9/16 - 18	0.39	2
42508N-688	81356	8C2AT-8RFJX45	1/2	3/4 - 16	0.56	2 1/4
42508N-690	-	-	1/2	7/8 - 14	0.64	2 1/2
42512N-692	81357	12C2AT-12RFJX45	3/4	1 1/16 - 12	0.73	2 13/16
42516N-696	-	-	1	1 5/16 - 12	0.89	3


**REUSABLE HYDRAULIC**

**REUSABLE COUPLINGS FOR 100R2 HOSE**

**SPECIFICATIONS**

PRODUCT I.D.			HOSE I.D. (IN.)	THREAD SIZE (IN.)	"T" DROP (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #	GATES REFERENCE #				
42504N-664	81358	4C2AT-4RFJX90	1/4	7/16 - 20	0.68	1 1/16
42506N-666	81359	6C2AT-6RFJX90	3/8	9/16 - 18	0.85	1 15/16
42508N-668	81361	8C2AT-8RFJX90	1/2	3/4 - 16	1.09	2 1/16
42508N-670	81362	8C2AT-10RFJX90	1/2	7/8 - 14	1.23	2 1/4
42512N-672	81363	12C2AT-12RFJX90	3/4	1 1/16 - 12	1.82	2 3/4
42516N-676	-	-	1	1 5/16 - 12	2.14	3 1/4


**Female JIC  
37° Flare Swivel  
90° Bent Tube**



**SPECIFICATIONS**

PRODUCT I.D.		HOSE I.D. (IN.)	THREAD SIZE (IN.)	"T" DROP (IN.)	"C" CUT-OFF (IN.)
RB&H #	GATES REFERENCE #				
42504N-644	4C2AT-4FJX90L	1/4	7/16 - 20	1.80	1 3/4
42506N-646	6C2AT-6FJX90L	3/8	9/16 - 18	2.18	2
42508N-648	6C2AT-8FJX90L	1/2	3/4 - 16	2.45	2 3/16
42512N-652	8C2AT-8FJX90L	3/4	1 1/16 - 12	3.75	2 3/4

**Female JIC  
37° Flare Swivel  
90° Bent Tube  
Long Drop**



**REUSABLE COUPLINGS FOR C1T HOSE**

**SAE 100R1 Type T, Thin Cover  
Non-Skive Type**

**SPECIFICATIONS**

PRODUCT I.D.		HOSE I.D. (IN.)	THREAD SIZE (IN.)	"C" CUT-OFF (IN.)
RB&H #	AUTOMOTIVE REFERENCE #			
4C1T-2RMP	81241	1/4	1/8 - 27	1.29
4C1T-4RMP	81210	1/4	1/4 - 18	1.51
6C1T-4RMP	81242	3/8	1/4 - 18	1.54
6C1T-6RMP	81211	3/8	3/8 - 18	1.39
8C1T-6RMP	81243	1/2	3/8 - 18	1.70
8C1T-8RMP	81212	1/2	1/2 - 14	1.71
8C1T-12RMP	81244	1/2	3/4 - 14	1.87
12C1T-12RMP	81213	3/4	3/4 - 14	1.73
16C1T-16RMP	81214	1	1 - 11 1/2	2.10

**NPTF Solid Male  
With 30° Cone Seat**

