

**INDUSTRIAL HOSE & FITTINGS**

**HOSE**

**Mill Discharge  
Hose Assemblies**



<b>SPECIFICATIONS</b>					
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	LENGTH (FT.)
1 1/2	MILL50-1-1/2	1.69	200	20	50
2 1/2	MILL50-2-1/2	2.88	200	40	50

APPLICATION: Water pump discharge or washdown service. Not recommended for fire fighting.

TUBE: Black rubber tube

COVER: Woven synthetic mildew resistant jacket.

TEMPERATURE: -40°F to 180°F

COUPLINGS: Pin lug (fire thread), adapters & nozzles

**Steam Hose**



<b>SPECIFICATIONS</b>					
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	LENGTH (FT.)
1/2	SH-450-250-1/2	62/64	250	.33	50
3/4	SH-450-250-3/4	1 16/64	250	.49	50
1	SH-450-250-1	1 32/64	250	.61	50
1 1/4	SH-450-250-1-1/4	1 52/64	250	.83	50
1 1/2	SH-450-250-1-1/2	2 9/64	250	1.03	50

APPLICATION: Recommended for cleaning, thawing, blowout service, steam pumps.

TUBE: Black synthetic rubber

REINFORCEMENT: Spiral plied steel wire.

COVER: Black synthetic rubber.

TEMPERATURE: 0°F to 406°F

COUPLINGS: Must use ground joint swivels.

**SAFETY ALERT**

**Ag Spray Economical**

BLACK BLENDED EPDM TUBE AND COVER



<b>SPECIFICATIONS</b>					
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	LENGTH (FT.)
1/4	AGSPRAY-1/4	.523	200	.11	500
3/8	AGSPRAY-3/8	.649	200	.15	500
1/2	AGSPRAY-1/2	.787	200	.19	500
5/8	AGSPRAY-5/8	.905	200	.24	500
3/4	AGSPRAY-3/4	1.063	200	.33	500
1	AGSPRAY-1	1.315	200	.42	500

APPLICATION: Agricultural chemical, water, and general service.

TUBE: Synthetic rubber, RMA Class C oil resistant

REINFORCEMENT: 2 fabric

COVER: Black synthetic rubber.

TEMPERATURE: -40°F to 190°F

COUPLINGS: Hose barb with clamps


**INDUSTRIAL HOSE & FITTINGS**

**HOSE**

**SPECIFICATIONS**

I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	LENGTH (FT.)
1	300EPDM-1	1.28	50	0.22	100
1 ¼	300EPDM-1-1/4	1.61	50	0.25	100
1 ½	300EPDM-1-1/2	1.88	50	0.44	100
2	300EPDM-2	2.50	50	0.79	100
2 ½	300EPDM-2-1/2	2.98	50	1.04	100
3	300EPDM-3	3.63	43	1.46	100
4	300EPDM-4	4.73	38	2.06	100
6	300EPDM-6	6.80	23	3.18	100

**Fertilizer Solution**



APPLICATION: Water suction & discharge hose, medium duty - agricultural, construction, general industrial, and vacuum truck service.

TUBE: Smooth EPDM rubber

COVER: Black with gray, yellow, or green helix.

TEMPERATURE: -30°F to 158°F

VACUUM: HG = 29"

COUPLINGS: Cam & groove, pin lug, king combination.

**SPECIFICATIONS**

I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	COLOR	LENGTH (FT.)
¼	NEPTUNE-3000-1/4-BK	.532	3,000	.16	Black	500
¾	NEPTUNE-3000-3/8-BK	.693	3,000	.24	Black	500
¼	NEPTUNE-3000-1/4-BL	.532	3,000	.16	Blue	500
¾	NEPTUNE-3000-3/8-BL	.693	3,000	.24	Blue	500

**Pressure Washer**

3,000 PSI

BLACK OR BLUE NON-MARKING



APPLICATION: Pressure washer machines.

TUBE: Black synthetic rubber.

COVER: Synthetic rubber RMA Class B oil resistant.

CONSTRUCTION: Braided one wire steel

TEMPERATURE: -20°F to 250°F

COUPLINGS: Permanent crimp couplings.



**SPECIFICATIONS**

I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (FT.)	COLOR	LENGTH (FT.)
¾	6PC3000BK	.68	3,000	.23	Black	300
¾	6PC4000BK	.68	4,000	.23	Black	300
½	8PC2500BK	.80	2,500	.28	Black	300
½	8PC4000BK	.86	4,000	.28	Black	300
¾	8PC3000BL	.68	3,000	.23	Blue	300
½	8PC4000BL	.86	4,000	.28	Blue	300

**Pressure Washer Hose**

BLACK OR BLUE NON-MARKING



APPLICATION: Medium pressure hose for hot or cold water high pressure cleaning equipment.

TUBE: Synthetic rubber.

COVER: Synthetic rubber, oil resistant.

REINFORCEMENT: High tensile steel one or two wire braid.

TEMPERATURE: -40°F to 212°F

COUPLINGS: Permanent crimp couplings.



**SPECIFICATIONS**

I.D. (IN.)	RB&H #	PSI	COLOR	LENGTH (FT.)
¾	3/8-50SWH	3,000	Black	50
¾	3/8-40SWH	3,000	Black	40
¾	3/8-25SWH	3,000	Black	25
¾	50PW-3/8	3,000	Black	50
¾	3/8-50SWH-BLUE	3,000	Blue	50

**Pressure Washer Hose Assemblies**



Pre-made assemblies coupled with male pipe or male pipe swivel with bend restrictors on each end. Black or blue non marking.



**INDUSTRIAL HOSE & FITTINGS**

**HOSE**

**Carpet Cleaning  
Hose**



**GOODYEAR**  
INDUSTRIAL HOSE

For van or truck mounted equipment. Blue non marking, will not scuff furniture or walls. Durable and abrasion resistant.

SPECIFICATIONS							
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	COMPOUND	WEIGHT (LBS./FT.)	BRAND	REEL LENGTH (FT.)
1/4	NEPTURE-3000-1/4-BL	.532	3,000	Rubber	.16	Goodyear	500

Uses permanent crimp couplings.  
Quick Disconnects on page 364.

**Shop Air Hose  
Assemblies**



**GOODYEAR**  
INDUSTRIAL HOSE

All quality air tool assemblies come complete with crimped on 1/4" male NPT brass nipples. Resistant to oil, abrasion, sunlight and ozone. Custom assemblies available.

SPECIFICATIONS							
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	COMPOUND	COLOR	BRAND	LENGTH (FT.)
3/8	3/8X25SA200	.669	200	Rubber	Red	Goodyear	25
3/8	3/8X50SA200	.669	200	Rubber	Red	Goodyear	50
3/8	3/8X25SA250	.700	250	Rubber	Red	Goodyear	25
3/8	3/8X50SA250	.700	250	Rubber	Red	Goodyear	50
3/8	3/8X25SABLUE	.639	300	PVC	Blue	Synflex	25
3/8	3/8X50SABLUE	.639	300	PVC	Blue	Synflex	50

**Air Whip Hose  
Assemblies**



For use with air tools, connects to tank and to your shop air hose for easy walk around. Red non-marking hose.

SPECIFICATIONS		
RB&H #	COLOR	LENGTH (IN.)
WHIP-HOSE-12	Red	12
WHIP-HOSE-24	Red	24
WHIP-HOSE-30	Red	30
WHIP-HOSE-PLUS-12	Blue	12
WHIP-HOSE-PLUS-24	Blue	24
WHIP-HOSE-PLUS-30	Blue	30

**Jack Hammer Hose  
Assemblies**



Custom made assemblies. Quick connect, universal couplings are banded with band clamps for optimal retention and safety. Heavy wall air hose resists the job site. Oil resistant tube handles fine oil mist and elevated compressor temperatures.

SPECIFICATIONS						
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	COLOR	WEIGHT (LBS.)	LENGTH (FT.)
3/4	JH-3/4RE	1.188	200	Red	.50	50
3/4	JH-3/4YE	1.188	250	Yellow	.39	50

**Contractor's Water  
Hose Assemblies**



Heavy duty black water hose assembled with brass GHT threaded couplings with crimped brass ferrules.

SPECIFICATIONS				
I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	LENGTH (FT.)
5/8	CWH-5/8	0.944	150	50
3/4	CWH-3/4	1.106	150	50

**INDUSTRIAL HOSE & FITTINGS**

**HOSE**

**SPECIFICATIONS**

I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	REINFORCED	COLOR	WEIGHT (FT.)	REEL LENGTH (FT.)
1/4	BFG-1/4-200R/R	.500	200	1 Braid	Red	.09	500
1/4	BFG-1/4-250R/R	.527	250	1 Braid	Red	.11	500
3/8	BFG-3/8-200R/R	.669	200	1 Braid	Red	.15	500
3/8	BFG-3/8-200B/R	.669	200	1 Braid	Black	.15	500
3/8	BFG-3/8-250R/R	.700	250	1 Braid	Red	.17	500
1/2	BFG-1/2-200R/R	.811	200	1 Braid	Red	.20	500
1/2	BFG-1/2-250R/R	.838	250	1 Braid	Red	.22	500
5/8	BFG-5/8-200R/R	1.00	200	1 Braid	Red	.27	500
5/8	BFG-5/8-250R/R	.976	250	1 Braid	Red	.27	500
3/4	BFG-3/4-200R/R	1.19	200	1 Braid	Red	.34	500
3/4	BFG-3/4-250R/R	1.19	250	1 Braid	Red	.35	500
1	BFG-1-200R/R	1.44	200	1 Braid	Red	.53	450
1	BFG-1-300R/R	1.48	300	1 Braid	Red	.58	450
1 1/4	BFG-1-1/4-200R/R	1.75	200	1 Braid	Red	.62	300
1 1/2	BFG-1-1/2-200R/R	2.00	200	1 Braid	Red	.73	300

**Air Hose Bulk**



**APPLICATION:** Air and water for a wide range of industrial, construction, and agricultural.  
**COVER:** Red or black.  
**TUBE:** Synthetic rubber RMA Class C, medium oil resistant.  
**TEMPERATURE:** -40°F to 190°F

**SPECIFICATIONS**

I.D. (IN.)	RB&H #	O.D. (IN.)	PSI	WEIGHT (LBS./FT.)	REEL LENGTH (FT.)
1/4	PLIOVIC-1/4	.500	250	.080	750
3/8	PLIOVIC-3/8	.656	250	.130	750
3/4	PLIOVIC-3/4	1.106	250	.280	450
1	PLIOVIC-1	1.378	250	.370	400

**Premium Air Hose Bulk**

PREMIUM AIR HOSE, BETTER OIL RESISTANCE



**APPLICATION:** Air, water and many spray solutions.  
**COVER:** Red Pliovic smooth finish RMA Class B.  
**TUBE:** Black Pliovic RMA Class B (medium/high oil resistance).  
**REINFORCEMENT:** Spiral synthetic yarn.  
**TEMPERATURE:** -10°F to 158°F  
**COUPLINGS:** Brass hose barbs.

**SPECIFICATIONS**

I.D. (IN.)	RB&H #	O.D. (IN.)	WEIGHT (LBS./FT.)	LENGTH (FT.)
1/2	HEATER-HOSE-08	.783	.17	50
5/8	HEATER-HOSE-10	.909	.22	50
3/4	HEATER-HOSE-12	1.035	.24	50
1	HEATER-HOSE-16	1.291	.38	50

**Heater Hose**



**APPLICATION:** Automotive and truck cooling systems.  
**COVER:** 2 spiral layers of reinforcement.  
**TUBE:** Black EPDM SAE 20R3 D2.  
**TEMPERATURE:** -40°F to 257°F  
**COUPLINGS:** Brass, aluminum, or steel hose barbs.